


Aluminium F-profile for 2 LED stripes

Track PRO-F 46/25/T22I

Radium

Product Datasheet Date: 20.04.2026



General Data

Article No.	TRPA1849
Codice	PROFILE M WING 46/25/B5C5 P 3M
Product EAN	4052899448773
Box quantity (pcs.)	4
EAN Box	4052899448780
Gross weight of box in kg	5.116
Length of box in m	3.02
Width of box in m	0.15
Height of box in m	0.15
Product weight	929 g
Product status	● Attivo

Specification

Type of accessory/spare part	Profile
Length max.	3000 mm
Length	3 m
Height	25 mm
Width	46 mm
Built-in width	26.5 mm
Internal width	24 mm
Material	Aluminium
no. of LED stripes in profile	2
Product shape	F

Aluminium F-profile for 2 LED stripes

Track PRO-F 46/25/T22I

Radium

Notes on Operation

Fitting Endcap	ZTPA2616, ZTPA2619, ZTPA4962
Fitting Cover	ZTPA1852
Fitting mounting clips or suspension	ZTPA1856

Notes

For cooling and protection of LED strips, width for 2 LED strips, suitable for various types of mounting (clips, springs, etc.), length adjustable.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.