
LED Star T5-RetroFit for ECG

RL-T5 54 HO 27W/840/G5 HF

Radium

Product Datasheet Date: 01.11.2026





A++ | 4100 | 4000K | 60 000h

General Data

Article No.	43319158
Codice	RL-T5 54 HO 27W/840/G5 HF
Product EAN	4008597191589
Box quantitiy (pcs.)	10
EAN Box	4008597491580
Gross weight of box in kg	2.2
Length of box in m	1.22
Width of box in m	0.15
Height of box in m	0.08
Product weight	160 g
Product status	Inattivo

Electric Parameters

Wattage	27.0 W
Weighted energy consumption in 1000 hours	30 kWh
Power factor	0.9
Nominal voltage	220-240 V
Mains Voltage	220 - 240 V

LED Star T5-RetroFit for ECG

RL-T5 54 HO 27W/840/G5 HF

Radium

Electric Parameters

Voltage type	AC
dimmable	No

Light Application Parameters

Rated lamp luminous flux	4100 lm
Lumen-Output mark	HO
Beam angle	160 °
Efficacy / Luminous efficiency	151.85 lm/W
Color temperature	4000 K
Colour rendering index CRI	80-89
Color Stability	≤ 4 sdcm

Service Life

Average life	60000 h
Mean service life	60000 h
Min. number of switching cycles	200000

Specification

Energylabel (E -> A++)	A++
Diameter	15 mm
Tube diameter	16 mm
Length	1149 mm
Length	1149 mm
Burning position	any
Shatterproof	Sì
Lamp shape	Tube, double-ended
Base	G5
Material	Glass
Colour	White
Housing colour	White

Notes on Operation

Degree of protection (IP)	IP20
Burning position	any
Mode of operation	ECG
Range of storage temperature	-20…+80 °C
Ambient temperatures	-20 ... +50°C

LED Star T5-RetroFit for ECG
RL-T5 54 HO 27W/840/G5 HF

Radium

Notes on Operation

With movement sensor	No

Information especially for EPREL

Lighting technology	LED
Directional or non-directional light	NDLS
Color tunable light source	No
Type of color temperature	SINGLE_VALUE
Life factor EPREL	0.9
Lumen maintenance EPREL	0.93

Notes

T5 tubular LED lamp for exchange with fluorescent lamps, neutral white light, glass bulb, non-dim, base G13. Operation with suitable ECG.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.
The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.
The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).


Base




G5
IEC/EN 60061-1
sheet 7004-52-5

Spectrum

As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.
The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.
White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin.
Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



LED retrofit tube lamps for fluorescent lamps 4000K



daylight(D 65)

Special features



General notes

LED Star T5-RetroFit for ECG

RL-T5 54 HO 27W/840/G5 HF

Please note the installation instructions when replacing fluorescent lamps with LED tubes. Some LED lamp types are only suitable for 1: 1 replacement at the reespective burning position: with CCG by using the enclosed starter, with ECG with compatible control gear. Others can be operated directly on 230V (conversion of the luminaire), others again can 'do' CCG as well as 230V or all 3 variations. Neo tubes need an external LED driver (replacement of the control gear). LED Neo tubes are dimmable, all other LED tubes are not dimmable.

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.
® = Registered trademark
Subject to change without notice. Errors and omissions excepted.

Safety instructions
To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.