


# Low voltage halogen pin base lamp

RJL 90W/12/SKY/GY6.35

# Radium

Product Datasheet Date: 06.04.2026



C



G



2380



2 000h



Dimmable

## General Data

Article No.	22319376
Codice	RJL 90W/12/SKY/GY6.35
Product EAN	4008597193767
Box quantity (pcs.)	40
EAN Box	4008597493768
Gross weight of box in kg	0.248
Length of box in m	0.142
Width of box in m	0.113
Height of box in m	0.105
Product weight	3 g
Product status	<span style="color: red;">●</span> Inattivo

## Electric Parameters

Wattage	90.0 W
Weighted energy consumption in 1000 hours	90 kWh
Nominal voltage	12 V
Lamp voltage	12-12 V
Nominal current	7500 mA

# Low voltage halogen pin base lamp

RJL 90W/12/SKY/GY6.35

**Radium**

## Electric Parameters

dimnable	Si
----------	----

## Light Application Parameters

Luminous flux	2380 lm
Rated lamp luminous flux	2380 lm
Colour temperature	3000 K

## Service Life

Average life	2000 h
No. switching cycles	50000

## Specification

Energylabel notice	old label, no EPREL registration, no EU data sheet
Energylabel (G -> A)	G
Energylabel (E -> A++)	C
Diameter	12 mm
Total length max.	44 mm
Burning position	any
Mercury content	0.0 mg
Model	Clear
Base	GY6.35

## Notes on Operation

Burning position	any
------------------	-----

## Information especially for EPREL

Energylabel notice	old label, no EPREL registration, no EU data sheet
EPREL ID number	863575

## Miscellaneous

EU-date of phase-out	01.09.2023
EU Directive	SLR = (EU) 2019/2020

## Notes

Standard low voltage halogen pin base lamp, 12V operation with transformer, base GY6.35, stepless dim, 2000 h mean service life

# Low voltage halogen pin base lamp

RJL 90W/12/SKY/GY6.35

**Radium**

Please, refer to [www.radium.de/recycling](http://www.radium.de/recycling) for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.


The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

# Low voltage halogen pin base lamp

RJL 90W/12/SKY/GY6.35

**Radium**

## Base




GY6.35  
IEC/EN 60061-1  
sheet 7004-59-6

## Spectrum


As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

Incandescent lamps have got a continuous red-dominated spectrum as the light is generated by heating up a tungsten filament. The addition of halogens to the filling gas enhance the efficiency and prevents blackening. Further increase in efficiency can be achieved by adding Xenon and/or IRC-coating.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.




light of incandescent lamps



daylight(D 65)

## Special features



## General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.