


Linear GLS lamp, clear
RAL2 120W/230/C/S14S

Radium

Product Datasheet Date: 16.12.2025





G



920



1 000h



Dimmable

General Data

Article No.	12710666
Codice	RAL2 120W/230/C/S14S
Product EAN	4008597106668
Box quantitiy (pcs.)	16
EAN Box	4008597406669
Gross weight of box in kg	4.013
Length of box in m	1.07
Width of box in m	0.23
Height of box in m	0.15
Product weight	173 g
Product status	 Inattivo

Electric Parameters

Wattage	120.0 W
Lamp nominal wattage	120 W
Power factor	1.00
Mains voltage	230 V
Nominal current (mA)	522 mA

Electric Parameters

dimmable	Si
----------	----

Light Application Parameters

Luminous flux	920 lm
Rated lamp luminous flux	920 lm
Efficacy	7.67 lm/W
Color rendering index	100

Service Life

Average life	1000 h
Mean service life	1000 h

Specification

Energylabel (G -> A)	G
Diameter	30 mm
Length	1000 mm
Total length max.	1000 mm
Burning position	any
Mercury content	0.0 mg
Model	Clear
Base	S14s

Notes on Operation

Burning position	any
------------------	-----

Miscellaneous

EU-date of phase-out	01.09.2013
EU Directive	DIM1

Notes

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.
The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.
The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Base

Linear GLS lamp, clear

RAL2 120W/230/C/S14S

Radium

S14s




IEC/EN 60061-1
sheet 7004-112-1

Spectrum


As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

Incandescent lamps have got a continuous red-dominated spectrum as the light is generated by heating up a tungsten filament.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



light of incandescent lamps



daylight(D 65)

Special features



General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.