
NL-T5 22W/840C/2GX13



Product Datasheet Date: 04.11.2025

















3

1800

4000K 12 000h

Dimmable

## **General Data**

Article No.	31218618
Codice	NL-T5 22W/840C/2GX13
Product EAN	4008597186189
Box quantitiy (pcs.)	12
EAN Box	4008597486180
Gross weight of box in kg	1.677
Length of box in m	0.3
Width of box in m	0.24
Height of box in m	0.25
Product weight	63 g
Product status	Inattivo

## **Electric Parameters**

Wattage	22.3 W
Lamp nominal wattage	22 W
Weighted energy consumption in 1000 hours	25 kWh
Lamp voltage	75 V
Mains voltage	230 V

NL-T5 22W/840C/2GX13



## **Electric Parameters**

Nominal current (mA)	300 mA
dimmable	Sì

## **Light Application Parameters**

Luminous flux	1900 lm	
Rated lamp luminous flux	1800 lm	
max. luminous flux	1900 lm	
max. luminous flux at	30 °C	
Beam angle	360 °	
Efficacy	85.2 lm/W	
Total mains efficacy	81 lm/W	
Light colour	white	
Code of light color	840	
Colour temperature	4000 K	
Color rendering index	? 80	
Mean luminance	1.7	
Lumen maintenance at 2000h	0.85	
Lumen maintenance at 4000h	0.83	
Lumen maintenance at 6000h	0.80	
Lumen maintenance at 8000h	0.80	
Lumen maintenance at 12000h	0.75	

### **Service Life**

Average life	12000 h
Lamp survival factor at 2000h	0.99
Lamp survival factor at 4000h	0.99
Lamp survival factor at 6000h	0.98
Lamp survival factor at 8000h	0.92
Lamp survival factor at 12000h	0.50

## **Specification**

Energylabel notice	old label, no EPREL registration, no EU data sheet
Energylabel (G -> A)	G
Energylabel (E -> A++)	A
Diameter max.	16 mm
Tube diameter	16 mm

NL-T5 22W/840C/2GX13



### **Specification**

Length	225 mm
Length	225 mm
Mercury content	3.7 mg
Lamp shape	Ring
Base	2GX13
Colour	White

### Information especially for EPREL

Energylabel notice	old label, no EPREL registration, no EU data sheet
EPREL ID number	866613

#### **Miscellaneous**

EU-date of phase-out	25.02.2023
EU Directive	RoHS

#### **Notes**

Fluorescent lamp Ring HE T5-16mm diameter, light colour 840, base 2GX13. Controllable by Dim-ECG.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

#### Base




2GX13 IEC/EN 60061-1 sheet 7004-125-1


#### Spectrum

Natural daylight is a mixture of direct sunlight and the light of the sky. Therefore, its spectral composition changes permanently due to the changing time of day. The standardised light classification D65 corresponds to a daylight with a colour temperature of approximately 6500 K. Every fluorescent lamp type has got an individual spectral power distribution according to its phosphor coating inside the bulb. From this result important properties light colour or colour rendering.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm) per 10nm.



light colour 840 Spectralux® white (21)




daylight(D 65)

NL-T5 22W/840C/2GX13



#### Circuit diagram(s)



One-lampe ciruit with electronic ballast

Key:

VG = ballast electronic (ECG)

P = phase

N = zero potential

Ctrl = Controller, dimmer

The required control gear (here electronic ballast) for the lamps operation is usually mounted in the suitable luminaire in an appropriate electric circuit. Changes of any kind are to be conducted by qualified and specialised staff, only. Thus, this circuit example is to be understood merely as a technical

background information for interested users.

#### Special features



#### General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.