

Driver for DC-LED lamps and modules

DRIVER 50W/1200mA IP20

Radium

Product Datasheet Date: 05.06.2026



General Data

Article No.	OTNA4035
Codice	DRIVER DC 50W/1200mA IP20
Product EAN	4003556010871
Box quantity (pcs.)	48
EAN Box	4003556410879
Gross weight of box in kg	9.8
Length of box in m	0.385
Width of box in m	0.285
Height of box in m	0.21
Product weight	186 g
Product status	● Attivo

Electric Parameters

Rated value output power max.	50.4 W
Output power	39.6-50.4 W
Power factor	≥0,95
Input voltage AC (range)	220-240 V
Input voltage DC (range)	200-280 V

Driver for DC-LED lamps and modules

DRIVER 50W/1200mA IP20

Radium

Electric Parameters

Output voltage	33-42 V
Surge voltage resistance (L - N)	1 kV
Inrush current	58 A
Output current	1200-1200 mA
Mains frequency	0 / 50 / 60 Hz
Suitable for DC-voltage (primary side)	Si
Content of harmonics (THD)	20 %
max. no. of lamps at 10A-B10 automatic fuse	9
max. no. of lamps at 16A-B16 automatic fuse	15
dimmable	No
Dimming with push-button	No

Service Life

Service life	70000 h
Lifetime @Tc max.	50000 h
Tc Temperature max.	73 °C
Lifetime @Tc mean	70000 h
Tc mean	68 °C
Lifetime @Tc low	100000 h
Tc low	63 °C
Guarantee	5 years

Specification

Mean efficiency	≥90% %
Length	245 mm
Height max.	21 mm
Width	30 mm
Material	metal
Model	Static

Notes on Operation

Degree of protection (IP)	IP20
Protection class	I
Mode of operation	Constant current
Type of connection	spring clamp
Range of storage temperature	-40...+80 °C

Driver for DC-LED lamps and modules

DRIVER 50W/1200mA IP20

Radium

Notes on Operation

Ambient temperatures	[-30...+50]
Tc Temperature max.	73 °C
max. relative air humidity	90 %
Max. no. of Neo36	4
Max. no. of Neo58	2

Miscellaneous

Similar products	OTNA4033, OTNA4034
------------------	--------------------

Notes

External constant current driver for installation in luminaire (e.g. for DC LED tubes), not dimmable, indoor use.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Special features



General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefs) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.