

LED driver DALI

DRIVER 4DIM 75W/200-1050MA IP54 OSRAM

Radium

Product Datasheet Date: 06.06.2026



General Data

Article No.	OTDA4050
Codice	DRIVER 4DIM 75W/200-1050MA IP54 OSRAM
Product EAN	4052899981942
Box quantity (pcs.)	20
EAN Box	4052899982031
Gross weight of box in kg	6.564
Length of box in m	0.609
Width of box in m	0.289
Height of box in m	0.118
Product weight	280 g
Product status	● Inattivo

Electric Parameters

Output voltage	24 V
dimnable	Si

Notes on Operation

Degree of protection (IP)	IP20
Protection class	II

Notes

4 channel constant voltage supply 24V, dimmable via DALI interface, for outdoor applications

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains

LED driver DALI

DRIVER 4DIM 75W/200-1050MA IP54 OSRAM

Radium

(frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

LED driver DALI

DRIVER 4DIM 75W/200-1050MA IP54 OSRAM

Radium

Special features



General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.