

# LED Essence+ Candle, frosted

RL-C40 HE 827/F/E14

# Radium

Product Datasheet Date: 18.04.2026



A



2700K



50 000h

## General Data

Article No.	44225341
Codice	RL-C40 HE 827/F/E14
Product EAN	4008597253416
Box quantity (pcs.)	10
EAN Box	4008597453410
Gross weight of box in kg	0.28
Length of box in m	0.205
Width of box in m	0.087
Height of box in m	0.123
Product weight	14 g
Product status	<span style="color: green;">●</span> Attivo

## Electric Parameters

Wattage	2.2 W
Weighted energy consumption in 1000 hours	3 kWh
Lamp power	2.2 W
Nominal voltage	220-240 V
Voltage type	AC

## Electric Parameters

Nominal current	21 mA
Nominal current (mA)	21 mA
Inrush current	3.52 A
max. no. of lamps at 10A automatic fuse	400
max. no. of lamps at 16A automatic fuse	640
dimnable	No

## Light Application Parameters

Luminous flux	470 lm
Rated luminous flux according to IEC 62612	470 lm
Luminous flux	470 lm
Lumen-Output mark	HE
Beam angle	330 °
Efficacy	214 lm/W
Total mains efficacy	214 lm/W
Color temperature	2700 K
Color coordinate X	0.463
Color coordinate Y	0.420
Color rendering index	≥ 80
Color Stability	≤ 6 sdc <sub>m</sub>

## Service Life

Average life	50000 h
Tc Temperature max.	60 °C
Min. number of switching cycles	25000

## Specification

Energylabel (G -> A)	A
Diameter	35 mm
Length	97 mm
Length	97 mm
Burning position	any
Photobiological safety according to EN 62471	RG0
Lamp shape	Candle
Base	E14
Colour	White

## Notes on Operation

Degree of protection (IP)	IP20
Burning position	any
Mode of operation	230 V
Ambient temperatures	-20 ... +40 °C
Tc Temperature max.	60 °C
With movement sensor	No

## Information especially for EPREL

Lighting technology	LED
Mains/Non mains connectable	MLS
Directional or non-directional light	NDLS
Color tunable light source	No
Type of color temperature	SINGLE_VALUE
Displacement factor EPREL	0,4
Life factor EPREL	0.9
Lumen maintenance EPREL	0.98
Flicker	1.0
Stroboscopic effect	0.4
EPREL ID number	2423057

## Notes

LED candle lamp, energy efficiency class A (HE), frosted glass bulb, dimmable, E14 base. LED light does not contain UV or IR radiation.

Please, refer to [www.radium.de/recycling](http://www.radium.de/recycling) for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).


## Spectrum

As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.


The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.

White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



LED-Retrofit-Lamps 2700K



daylight(D 65)

# LED Essence+ Candle, frosted

## RL-C40 HE 827/F/E14

# Radium

### Special features



### General notes

For LED replacement of halogen and incandescent lamps, we recommend direct replacement (1: 1) at the respective burning position. For new systems, the number of lamps in the circuit operated at control gear such as transformers or dimmers can be obtained from corresponding compatibility lists (if available). If there is no specification for the type of device or lamp required, for safety reasons, the replacement power shall be assumed as that of the original halogen type (eg "RL-MR16 35" -> 35W, independent of the real power consumption).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefs) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

### Safety instructions

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.