

# LED Grid Luminaire Star, Panel 625

30W PS CCT UGR IP40

# Radium

Product Datasheet Date: 24.04.2026



30004000K

## General Data

Article No.	PNLA5082
Codice	PL S 625 30W PS CCT UGR IP40
Product EAN	4003556015128
Box quantity (pcs.)	6
EAN Box	4003556415126
Gross weight of box in kg	14.28
Length of box in m	0.68
Width of box in m	0.24
Height of box in m	0.643
Product weight	1870 g
Product status	● Attivo

## Electric Parameters

Max. system power	30.0 W
Nominal voltage	220-240 V
Voltage type	AC
Nominal current	152-800 mA
Nominal current (mA)	800 mA

## Electric Parameters

Number of poles	2
Inrush current	31 A
Mains frequency	50/60 Hz Hz
Dimming with push-button	No

## Light Application Parameters

Luminous flux adjustable	Positions
Luminous flux	4500 lm
Rated luminous flux according to IEC 62722-2-1	4500 lm
Luminous flux @3000K	3150-4180 lm
Luminous flux @4000K	3400-4500 lm
Beam angle adjustable	No
Beam angle	85 °
Unified Glare Ratio (UGR)	19
Efficacy	150 lm/W
Total mains efficacy	150 lm/W
Colour of light adjustable	Positions
CCT Switch	Si
Colour of light	RGBW
Color temperature	3000 / 4000 K
Color coordinate X	0.382
Color coordinate Y	0.398
Color rendering index	≥ 80
Color Stability	≤ 3 sdcms
Light sharing	Symmetric
With light sensor	No

## Service Life

Lifetime L70B50	70000 h
Life L80B10	70000 h
No. switching cycles	≥ 100.000
Guarantee	5

## Specification

Length	620 mm
Height/depth	34 mm

## Specification

Width	620 mm
Material	Aluminium/ PS
Impact strength	IK02
Photobiological safety according to EN 62471	RG0
With light source	Si
Exchangeable control gear	Si

## Notes on Operation

Degree of protection (IP)	IP40
Connection type	Push-in clamp
Type of wiring	Suitable for through wiring
Max. number of luminaires per B10 circuit breaker	23
Max. number of luminaires per B16 circuit breaker	36
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24	No
Filament test according to IEC 60695-2-11	650 °C - 30 s
Type of control gear	LED operating device voltage-controlled
With light sensor	No
With movement sensor	No
Suitable for emergency lighting	No
Emergency power supply integrated	Si

## Information especially for EPREL

Contains a lightsource of energy efficiency class	C
Mains/Non mains connectable	MLS
Directional or non-directional light	NDLS
Color tunable light source	Si
Type of color temperature	STEPS
Flickering value Pst LM	1
Stroboscope effect value SVM	0.4
EPREL ID number	2655161

## Notes

Flat IP40 LED retrofit panel 625x625 mm, integrated LED driver with power select, low glare (UGR), adjustable light color (steps)

Please, refer to [www.radium.de/recycling](http://www.radium.de/recycling) for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

# LED Grid Luminaire Star, Panel 625

30W PS CCT UGR IP40

# Radium

## Special features



## General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.