

# LED Highbay Luminaire Star DALI IP65

200W PS CCT BS

# Radium

Product Datasheet Date: 24.04.2026



40006500K

## General Data

|                |                              |
|----------------|------------------------------|
| Article No.    | HIBA5116                     |
| Codice         | HB S DALI 200 PS CCT BS IP65 |
| Product EAN    | 4003556015463                |
| Product weight | 2575 g                       |
| Product status | ● Attivo                     |

## Electric Parameters

|                          |             |
|--------------------------|-------------|
| Max. system power        | 200.0 W     |
| Power steps              | 200.0 W     |
| Nominal voltage          | 220-240 V   |
| Voltage type             | AC          |
| Nominal current          | 1035-800 mA |
| Nominal current (mA)     | 800 mA      |
| Number of poles          | 2           |
| Inrush current           | 140 A       |
| Mains frequency          | 50/60 Hz Hz |
| Dimming with push-button | No          |
| Power Select             | Si          |

## Light Application Parameters

|  |                      |
|--|----------------------|
| Luminous flux adjustable                       | Positions            |
| Luminous flux                                  | 32000 lm             |
| Rated luminous flux according to IEC 62722-2-1 | 32000 lm             |
| Luminous flux @4000K                           | 19200-32000 lm       |
| Luminous flux Q 6000/6500K                     | 19200-32000 lm       |
| Beam angle adjustable                          | Positions            |
| Efficacy                                       | 160 lm/W             |
| Total mains efficacy                           | 160 lm/W             |
| Colour of light adjustable                     | Positions            |
| CCT Switch                                     | Si                   |
| Colour of light                                | White                |
| Color temperature                              | 4000 / 5000 / 6500 K |
| Color coordinate X                             | 0.382                |
| Color coordinate Y                             | 0.398                |
| Color rendering index                          | ≥ 80                 |
| Color Stability                                | ≤ 6 sdc <sub>m</sub> |
| Light sharing                                  | Symmetric            |

## Service Life

|                      |         |
|----------------------|---------|
| Lifetime L70B50      | 80000 h |
| Life L80B10          | 80000 h |
| No. switching cycles | ≥100000 |
| Guarantee            | 5       |

## Specification

|  |                |
|--|----------------|
| Diameter                                     | 322 mm         |
| Length                                       | 322 mm         |
| Height/depth                                 | 157 mm         |
| Width  | 322 mm         |
| Installation height max.                     | max. 15 m      |
| Material                                     | Aluminium / PC |
| Impact strength                              | IK08           |
| Photobiological safety according to EN 62471 | RG1            |
| With light source                            | Si             |
| Exchangeable control gear                    | No             |

## Notes on Operation

|   |   |
|---|---|
| Degree of protection (IP)   | IP65                                    |
| Connection type   | Other                                   |
| Type of wiring  | Ending                                  |
| Max. number of luminaires per B10 circuit breaker                               | 4                                       |
| Max. number of luminaires per B16 circuit breaker                               | 7                                       |
| Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 | No                                      |
| Filament test according to IEC 60695-2-11                                       | 650 °C - 30 s                           |
| Mounting method   | Pendant                                 |
| Type of control gear  | LED operating device voltage-controlled |
| Suitable for emergency lighting   | No                                      |
| Emergency power supply integrated   | No                                      |

## Information especially for EPREL

|   |         |
|---|---------|
| Contains a lightsource of energy efficiency class | C       |
| Mains/Non mains connectable                       | MLS     |
| Directional or non-directional light              | NDLS    |
| Color tunable light source                        | Si      |
| Type of color temperature                         | STEPS   |
| Flicker   | 1.0     |
| Stroboscopic effect                               | 0.4     |
| EPREL ID number                                   | 2655295 |

## Notes

DALI Highbay luminaire for halls and large areas, integrated LED driver with power select, low glare, adjustable light color and beam angle (steps)

Please, refer to [www.radium.de/recycling](http://www.radium.de/recycling) for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

### Special features



### General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

# LED Highbay Luminaire Star DALI IP65

200W PS CCT BS

**Radium**

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.