


# LED Essence Pin

RL-PIN20 1,7W/12/WFL/827/G4

# Radium

Product Datasheet Date: 03.06.2026



A++



F



200



2700K



15 000h

## General Data

Article No.	42619086
Kod	RL-PIN20 827/G4
Product EAN	4008597190865
Box quantity (pcs.)	20
EAN Box	4008597490866
Gross weight of box in kg	0.256
Length of box in m	0.15
Width of box in m	0.12
Height of box in m	0.08
Product weight	6 g
Product status	<span style="color: red;">●</span> Nieaktywne

## Electric Parameters

Wattage	1.7 W
Weighted energy consumption in 1000 hours	2 kWh
Lamp power	1.7-1.7 W
Power factor	> 0,5
Nominal voltage	11.5-12 V

# LED Essence Pin

RL-PIN20 1,7W/12/WFL/827/G4

**Radium**

## Electric Parameters

Voltage type	AC
Nominal current	235-235 mA
Nominal current (mA)	235 mA
dimnable	Nie

## Light Application Parameters

Rated lamp luminous flux	200 lm
Luminous flux in 90°-sector	200 lm
Beam angle	300 °
Efficacy / Luminous efficiency	117.65 lm/W
Total mains efficacy	117.65 lm/W
Light colour	warmwhite
Color temperature	2700 K
Color rendering index	≥ 80
Color Stability	≤ 6 sdc <sub>m</sub>

## Service Life

Average life	15000 h
Mean service life	15000 h
No. switching cycles	100000

## Specification

Energylabel notice	old label, no EPREL registration, no EU data sheet
Energylabel (G -> A)	F
Energylabel (E -> A++)	A++
Diameter	14 mm
Length	36 mm
Length	36 mm
Burning position	any
Mercury content	0.0 mg
Lamp shape	Capsule
Base	G4
Colour	White

## Notes on Operation

Degree of protection (IP)	IP20
Burning position	any

# LED Essence Pin

RL-PIN20 1,7W/12/WFL/827/G4

# Radium

## Notes on Operation

Mode of operation	LV transformer
With movement sensor	Nie

## Information especially for EPREL

Energylabel notice	old label, no EPREL registration, no EU data sheet
Lighting technology	LED
Color tunable light source	Nie
Life factor EPREL	0.9
Lumen maintenance EPREL	0.93
EPREL ID number	1426676

## Notes

LED PIN, LED lamp for exchange with pin-base halogen lamps, base G4. LED light does not contain UV or IR radiation.

Please, refer to [www.radium.de/recycling](http://www.radium.de/recycling) for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

### Base



G4  
IEC/EN 60061-1  
sheet 7004-72-3


### Spectrum

As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.


The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.

White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.




LED retrofit pin lamps 2700K



daylight(D 65)

### Special features



# LED Essence Pin

RL-PIN20 1,7W/12/WFL/827/G4

**Radium**

## General notes

For LED replacement of halogen and incandescent lamps, we recommend direct replacement (1: 1) at the respective burning position. For new systems, the number of lamps in the circuit operated at control gear such as transformers or dimmers can be obtained from corresponding compatibility lists (if available). If there is no specification for the type of device or lamp required, for safety reasons, the replacement power shall be assumed as that of the original halogen type (eg "RL-MR16 35" -> 35W, independent of the real power consumption).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefs) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

## Safety instructions

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.