

LED Star PAR16

RL-PAR16 80 DIM 840/WFL/GU10

Radium

Product Datasheet Date: 20.04.2026



General Data

| | |
|---------------------------|---|
| Article No. | 43519198 |
| Kod | RL-PAR16 80 DIM 840/WFL |
| Product EAN | 4008597191985 |
| Box quantity (pcs.) | 10 |
| EAN Box | 4008597491986 |
| Gross weight of box in kg | 0.69 |
| Length of box in m | 0.253 |
| Width of box in m | 0.107 |
| Height of box in m | 0.068 |
| Product weight | 56 g |
| Product status | ● Nieaktywne |

Electric Parameters

| | |
|---|-----------|
| Wattage | 8.0 W |
| Nominal power | 8.0 W |
| Weighted energy consumption in 1000 hours | 8 kWh |
| Lamp power | 8.0-8.0 W |
| Power factor | > 0,8 |

LED Star PAR16

RL-PAR16 80 DIM 840/WFL/GU10

Radium

Electric Parameters

| | |
|----------------------|-------------|
| Nominal voltage | 220-240 V |
| Mains Voltage | 220 - 240 V |
| Voltage type | AC |
| Nominal current | 47-47 mA |
| Nominal current (mA) | 47 mA |
| dimnable | Tak |

Light Application Parameters

| | |
|-------------------------------|------------|
| Luminous flux | 575 lm |
| Rated lamp luminous flux | 575 lm |
| Luminous flux in 90°-sector | 575 lm |
| Luminous intensity | 1439 cd |
| Beam angle | 36 ° |
| Efficacy | 71,88 lm/W |
| Total mains efficacy | 71,88 lm/W |
| Color temperature | 4000 K |
| Color rendering index | ≥ 80 |
| Color rendering index nominal | 80 |
| Color Stability | ≤ 5 sdcn |

Service Life

| | |
|-------------------------------|---------|
| Average life | 25000 h |
| Mean service life | 25000 h |
| No. switching cycles | 100000 |
| Lamp survival factor at 6000h | ≥ 0.90 |
| Early failure rate at 1000h | ≤5.0% |
| Guarantee | 5 years |

Specification

| | |
|------------------------|--|
| Energylabel notice | old label, no EPREL registration, no EU data sheet |
| Energylabel (E -> A++) | A+ |
| Diameter | 51 mm |
| Length | 55 mm |
| Length | 55 mm |
| Burning position | any |
| Mercury content | 0.0 mg |

Specification

| | |
|--|-----------|
| Photobiological safety according to EN 62471 | RG1 |
| Lamp shape | Reflector |
| Base | GU10 |
| Colour | White |

Notes on Operation

| | |
|---------------------------|--------------|
| Degree of protection (IP) | IP20 |
| Burning position | any |
| Mode of operation | 230 V |
| Ambient temperatures | -20...+40 °C |
| With movement sensor | Nie |

Information especially for EPREL

| | |
|--------------------------------------|--|
| Energylabel notice | old label, no EPREL registration, no EU data sheet |
| Lighting technology | LED |
| Mains/Non mains connectable | MLS |
| Directional or non-directional light | DLS |
| Color tunable light source | Nie |
| Type of color temperature | SINGLE_VALUE |
| Flicker | 1.0 |
| Stroboscopic effect | 0.4 |

Notes

PAR16-LED for exchange with halogen lamps, neutral white light, glass bulb, dimmable, base GU10. LED light does not contain UV or IR radiation.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Base



GU10
IEC/EN 60061-1
sheet 7004-121-1

Spectrum

As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.

White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin.

