



General Data

Article No.	OTNA2420
Kod	DRIVER 40W/24V IP66 OSRAM
Product EAN	4052899545946
Box quantity (pcs.)	20
EAN Box	4052899545953
Gross weight of box in kg	9.176
Length of box in m	0.35
Width of box in m	0.31
Height of box in m	0.19
Product weight	416 g
Product status	● Nieaktywne

Electric Parameters

Rated value output power max.	40.0 W
min. output power	0.4 W
Output power	0-40.0 W
Power factor	0,95
Input voltage AC (range)	198-264 V
Output Voltage	24,2 V
Output voltage	24-24 V
Surge voltage resistance (L - N)	4 kV
Number of Channels	1
Supply frequency	0/50/60 Hz

Electric Parameters

Suitable for DC-voltage (primary side)	Tak
max. no. of lamps at 10A-B10 automatic fuse	35
max. no. of lamps at 16A-B16 automatic fuse	57
dimmable	Nie
Dimming with push-button	Nie

Service Life

Service life	50000 h
Tc Temperature max.	85 °C

Specification

Mean efficiency	85 %
Length	208 mm
Height max.	26 mm
Width	43 mm
Material	Plastic
Model	Static

Notes on Operation

Degree of protection (IP)	IP66
Type of connection	Cable
Ambient temperatures	-30...+55 °C
Tc Temperature max.	85 °C

Notes

Constant voltage supply 24V, not dimmable, for outdoor applications

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Special features



General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment

LED Strip operational gear

DRIVER 40W/24V IP66 OSRAM

Radium

valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.