

# Halogen lamp double based

RJH-TS 80W/230/C/XE/R7S

# Radium

Product Datasheet Date: 18.06.2026



G



1395



2900K



2 000h



Dimmable

## General Data

Article No.	22315971
Kod	RJH-TS 80W/230/C/XE/R7S
Product EAN	4008597159718
Box quantity (pcs.)	20
EAN Box	4008597459719
Gross weight of box in kg	0.193
Length of box in m	0.113
Width of box in m	0.093
Height of box in m	0.073
Product weight	6 g
Product status	<span style="color: green;">●</span> Aktywne

## Electric Parameters

Wattage	80.0 W
Lamp nominal wattage	80 W
Weighted energy consumption in 1000 hours	80 kWh
Lamp voltage	220-240 V
Mains voltage	230 V

## Electric Parameters

Lamp's nominal current	0.35 A
Nominal current (mA)	347 mA
dimnable	Tak

## Light Application Parameters

Luminous flux	1385 lm
Rated lamp luminous flux	1395 lm
Efficacy / Luminous efficiency	17 lm/W
Colour temperature	2900 K
Color coordinate X	0.446
Color coordinate Y	0.407
Color rendering index	100

## Service Life

Average life	2000 h
No. switching cycles	10000

## Specification

Energylabel notice	current label, with EPREL registration
Energylabel (G -> A)	G
Diameter	12 mm
Length	81 mm
Total length max.	80.3 mm
Length	80.3 mm
Contact distance l	74.9 mm
Burning position	any
Mercury content	0.0 mg
Lamp shape	Tube, double-ended
Model	Clear
Base	R7s

## Notes on Operation

Burning position	any
------------------	-----

## Information especially for EPREL

Energylabel notice	current label, with EPREL registration
--------------------	--

# Halogen lamp double based

RJH-TS 80W/230/C/XE/R7S

# Radium

---

Lighting technology

HL

---

Mains/Non mains connectable

MLS

---

## Information especially for EPREL

Directional or non-directional light	NDLS
EPREL ID number	566079

## Miscellaneous

Similar products	22315970, 22315972
------------------	--------------------

## Notes

Mains voltage halogen lamp clear, tubular shape, 230V mains, double ended, base R7s, dimmable steplessly

Please, refer to [www.radium.de/recycling](http://www.radium.de/recycling) for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

### Base




R7s  
IEC/EN 60061-1  
sheet 7004-92A-4

### Spectrum

As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

Incandescent lamps have got a continuous red-dominated spectrum as the light is generated by heating up a tungsten filament. The addition of halogens to the filling gas enhance the efficiency and prevents blackening. Further increase in efficiency can be achieved by adding Xenon and/or IRC-coating.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.




light of incandescent lamps



daylight(D 65)

### Special features



### General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment

# Halogen lamp double based

RJH-TS 80W/230/C/XE/R7S

# Radium

valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.