



F



3400



6500K



24 000h



Dimmable

## General Data

Article No.	31119581
Kod	NL-T5 35W/865/G5
Product EAN	4008597195815
Box quantity (pcs.)	20
EAN Box	4008597595813
Gross weight of box in kg	3.09
Length of box in m	1.511
Width of box in m	0.104
Height of box in m	0.088
Product weight	116 g
Product status	<span style="color: red;">●</span> Nieaktywne

## Electric Parameters

Wattage	35.0 W
Lamp nominal wattage	35 W
Weighted energy consumption in 1000 hours	35 kWh
Lamp voltage	205 V
Mains voltage	230 V

## Electric Parameters

Nominal current (mA)	175 mA
dimnable	Tak

## Light Application Parameters

Luminous flux	3050 lm
Rated lamp luminous flux	3400 lm
max. luminous flux	3500 lm
max. luminous flux at	35 °C
Beam angle	360 °
Efficacy	97 lm/W
Total mains efficacy	97 lm/W
Light colour	daylight
Code of light color	865
Colour temperature	6500 K
Color coordinate X	0,313
Color coordinate Y	0,337
Color rendering index	? 80
Mean luminance	1.7
Lumen maintenance at 2000h	0.95
Lumen maintenance at 4000h	0.93
Lumen maintenance at 6000h	0.92
Lumen maintenance at 8000h	0.90
Lumen maintenance at 12000h	0.90
Lumen maintenance at 16000h	0.90
Lumen maintenance at 20000h	0.89

## Service Life

Average life	24000 h
Lamp survival factor at 2000h	0.99
Lamp survival factor at 4000h	0.99
Lamp survival factor at 6000h	0.99
Lamp survival factor at 8000h	0.99
Lamp survival factor at 12000h	0.99
Lamp survival factor at 16000h	0.97
Lamp survival factor at 20000h	0.85

## Specification

Energylabel notice	current label, with EPREL registration
Energylabel (G -> A)	F
Diameter max.	16 mm
Tube diameter	16 mm
Length max.	1463,2 mm
Length	1449 mm
Mercury content	1.5 mg
Lamp shape	Rod
Base	G5
Colour	White

## Notes on Operation

Suitable for emergency lighting	Nie
---------------------------------	-----

## Information especially for EPREL

Energylabel notice	current label, with EPREL registration
EPREL ID number	541107

## Miscellaneous

EU-date of phase-out	25.08.2023
EU Directive	RoHS
Similar products	31119582, 31119583

## Notes

Fluorescent lamp HE T5-16mm diameter, light colour 865, high luminous efficiency, good colour rendering, long life, base G5. Controllable by Dim-ECG.

Please, refer to [www.radium.de/recycling](http://www.radium.de/recycling) for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

### Base



G5  
IEC/EN 60061-1  
sheet 7004-52-5

### Spectrum

Natural daylight is a mixture of direct sunlight and the light of the sky. Therefore, its spectral composition changes permanently due to the changing time of day. The standardised light classification D65 corresponds to a daylight with a colour temperature of approximately 6500 K.

Every fluorescent lamp type has got an individual spectral power distribution according to its phosphor coating inside the bulb. From this result


# Fluorescent lamp Bonalux®

NL-T5 35W/865/G5

# Radium

important properties light colour or colour rendering.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm) per 10nm.




light colour 865 Spectralux® daylight (11)



daylight(D 65)

## Circuit diagram(s)



One-lampe circuit with electronic ballast

Key:

VG = ballast electronic (ECG)

P = phase

N = zero potential

Ctrl = Controller, dimmer

The required control gear (here electronic ballast) for the lamps operation is usually mounted in the suitable luminaire in an appropriate electric circuit. Changes of any kind are to be conducted by qualified and specialised staff, only. Thus, this circuit example is to be understood merely as a technical

background information for interested users.

## Special features



## General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.