
RL-T8 36 S 840/G13 HF



Product Datasheet Date: 03.12.2025

















[D]

2100

4000K 60 000h

General Data

Article No.	43720059
Kod	RL-T8 36 S 840/G13 HF
Product EAN	4008597200595
Box quantitiy (pcs.)	10
EAN Box	4008597600593
Gross weight of box in kg	2.865
Length of box in m	1.272
Width of box in m	0.21
Height of box in m	0.115
Product weight	200 g
Product status	Aktywne

Electric Parameters

Wattage	14.0 W
Nominal power	14.0 W
Weighted energy consumption in 1000 hours	14 kWh
Lamp power	14.0-14.0 W
Power factor	> 0.9

RL-T8 36 S 840/G13 HF



Electric Parameters

Nominal voltage	40-70 V	
Mains Voltage	220 - 240 V	
Voltage type	AC	
Nominal current	80-80 mA	
Nominal current (mA)	80 mA	
Inrush current	20 A	
dimmable	Nie	

Light Application Parameters

Luminous flux	2100 lm	
Rated lamp luminous flux	2100 lm	
Beam angle	190 °	
Efficacy	150 lm/W	
Total mains efficacy	150 lm/W	
Light colour	coolwhite	
Color temperature	4000 K	
Color coordinate X	0,381	
Color coordinate Y	0,379	
Color rendering index	≥ 80	
Color rendering index nominal	83	
Color Stability	≤ 5 sdcm	

Service Life

Average life	60000 h
Tc Temperature max.	68 °C
Mean service life	60000 h
Lifetime L70B50	60000 h
max. temperature at Tc -point for nominal life with ECG	45 °C
Life L70 @ Tc max. with ECG	38000 h
Tc max. with ECG	68 °C
No. switching cycles	200000
Lamp survival factor at 6000h	≥ 0.90
Early failure rate at 1000h	≤ 5.0 %
Guarantee	5 years

RL-T8 36 S 840/G13 HF



Specification

Energylabel notice	current label, with EPREL registration
Energylabel (G -> A)	[D]
Diameter	27,8 mm
Tube diameter	26 mm
Length	1212 mm
Length	1200 mm
Burning position	any
Mercury content	0.0 mg
Shatterproof	Tak
Photobiological safety according to EN 62471	RG0
Lamp shape	Tube, double-ended
Base	G13
Colour	White

Notes on Operation

Degree of protection (IP)	IP20
Burning position	any
Mode of operation	ECG
Ambient temperatures	-20 +45 °C
Tc Temperature max.	68 °C
Tc max. with ECG	68 °C
max. temperature at Tc -point for nominal life with ECG	45 °C

Information especially for EPREL

Energylabel notice	current label, with EPREL registration
Lighting technology	LED
Color tunable light source	Nie
Type of color temperature	SINGLE_VALUE
Color stability MacAdams EPREL	5
Displacement factor EPREL	0,9
Life factor EPREL	0,9
Lumen maintenance EPREL	0,7
EPREL ID number	541585

RL-T8 36 S 840/G13 HF



Miscellaneous

Similar products

43719733, 43719728, 43920142, 43719850

Notes

T8 tubular LED lamp for exchange with fluorescent lamps, neutral white light, glass bulb, non-dim, base G13. Operation with suitable ECG only.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).




Spectrum


As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.

White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin. Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



LED retrofit tube lamps for fluorescent lamps 4000K



Special features









General notes

Please note the installation instructions when replacing fluorescent lamps with LED tubes. Some LED lamp types are only suitable for 1: 1 replacement at the reespective burning position: with CCG by using the enclosed starter, with ECG with compatible control gear. Others can be operated directly on 230V (conversion of the luminaire), others again can 'do' CCG as well as 230V or all 3 variations. Neo tubes need an external LED driver (replacement of the control gear). LED Neo tubes are dimmable, all other LED tubes are not dimmable.

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

RL-T8 36 S 840/G13 HF



Subject to change without notice. Errors and omissions excepted.

Safety instructions

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.