
# **High pressure sodium lamp** RNP-E/LR 70W/S/230/E27



Product Datasheet Date: 19.10.2025













30 000h



6600

2000K

Dimmable

#### **General Data**

Article No.	34419711
Kod	RNP-E/LR 70W/S/230/E27
Product EAN	4008597197116
Box quantitiy (pcs.)	24
EAN Box	4008597497117
Gross weight of box in kg	1.919
Length of box in m	0.36
Width of box in m	0.285
Height of box in m	0.355
Product weight	50 g
Product status	Aktywne

## **Electric Parameters**

Wattage	75.4 W
Weighted energy consumption in 1000 hours	76 kWh
Lamp voltage	90 V
Mains voltage	230 V
Ignition voltage	1.8 up to 5.0

# **High pressure sodium lamp** RNP-E/LR 70W/S/230/E27



## **Electric Parameters**

Nominal current (A)	0.98 A
Nominal choke current	1 A
Compensation capacitor for 50Hz operation	12 μF
Fuse	Daelay-action; min. double nominal current
dimmable	Tak

## **Light Application Parameters**

Luminous flux	6400 lm	
Rated lamp luminous flux	6600 lm	
Efficacy	85 lm/W	
Total mains efficacy	79 lm/W	
Colour temperature	2000 K	
Color coordinate X	0,535	
Color coordinate Y	0.420	
Color rendering index	< 25	
Lumen maintenance at 2000h	0.98	
Lumen maintenance at 4000h	0.91	
Lumen maintenance at 6000h	0.90	
Lumen maintenance at 8000h	0.89	
Lumen maintenance at 12000h	0.88	
Lumen maintenance at 16000h	0.86	
Lumen maintenance at 20000h	0.85	

## **Service Life**

Average life	30000 h	
B5 - Service life 5% failures	16000 h	
B10 - Service life 10% failures	20000 h	
Lamp survival factor at 2000h	0.99	
Lamp survival factor at 4000h	0.98	
Lamp survival factor at 6000h	[0.98]	
Lamp survival factor at 8000h	0.98	
Lamp survival factor at 12000h	0.97	
Lamp survival factor at 16000h	0.96	
Lamp survival factor at 20000h	0.96	

# **High pressure sodium lamp**

RNP-E/LR 70W/S/230/E27



### **Specification**

Energylabel notice	current label, with EPREL registration
Energylabel (G -> A)	G
Diameter	71 mm
Length	156 mm
Total length max.	156 mm
Burning position	h180
Mercury content	19.0 mg
Lamp shape	Ellipsoid
Model	Opal
Base	E27

#### **Notes on Operation**

Burning position	h180	

### Information especially for EPREL

Energylabel notice	current label, with EPREL registration
EPREL ID number	541489

#### **Miscellaneous**

Similar products	34416043	

#### **Notes**

High pressure sodium lamp long run (4Y), elliptical bulb coated, base E27. Operation with ballast and ignitor.

Please, refer to <a href="www.radium.de/recycling">www.radium.de/recycling</a> for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

#### Base



IEC/EN 60061-1 sheet 7004-21-9

#### Spectrum

Natural daylight is a mixture of direct sunlight and the light of the sky. Therefore, its spectral composition changes permanently due to the changing time of day. The standardised light classification D65 corresponds to a daylight with a colour temperature of approximately 6500 K. Every discharge lamp type has got an individual spectral power distribution according to its chemical filling. From this result important properties light colour or colour rendering. Sodium vapour lamps are very economic, due to the yellow light RNP lamps have got a high luminous efficiency but only


# High pressure sodium lamp

RNP-E/LR 70W/S/230/E27




modest colour rendering.

After the lamp start a high pressure sodium lamp needs about 6-10 minutes time to reach its full luminous flux. Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



RNP Standard/Super



daylight(D 65)

#### Special features





#### General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.