
RL-T8 18 865/G13 EM



Product Datasheet Date: 03.12.2025











800







6,6

,6

6500K

30 000h

General Data

Article No.	43819741
Kod	RL-T8 18 865/G13 EM
Product EAN	4008597197413
Box quantitiy (pcs.)	10
EAN Box	4008597597411
Gross weight of box in kg	1.589
Length of box in m	0.69
Width of box in m	0.21
Height of box in m	0.115
Product weight	100 g
Product status	Nieaktywne

Electric Parameters

Wattage	6.6 W	
Nominal power	6.6 W	
Weighted energy consumption in 1000 hours	7 kWh	
Lamp power	6.6 W	
Power factor	> 0.9	

RL-T8 18 865/G13 EM



Electric Parameters

Nominal voltage	220-240 V
Voltage type	AC
Nominal current (mA)	35 mA
max. no. of lamps at 10A automatic fuse	40
max. no. of lamps at 16A automatic fuse	50
dimmable	Nie

Light Application Parameters

Luminous flux	800 lm
Rated lamp luminous flux	800 lm
Beam angle	190 °
Efficacy	121 lm/W
Total mains efficacy	133 lm/W
Color temperature	6500 K
Color coordinate X	0.312
Color coordinate Y	0.328
Color rendering index	≥ 80
Color rendering index nominal	80
Color Stability	≤ 6 sdcm

Service Life

Average life	30000 h
Tc Temperature max.	65 °C
Mean service life	30000 h
Lifetime L70B50	30000 h
max. temperature at Tc -point for nominal life with CCG or 230V AC	60 °C
Life L70 @ Tc max. with CCG or 230V AC	26000 h
Tc max. with CCG or 230V AC	65 °C
No. switching cycles	200000
Lamp survival factor at 6000h	≥ 0.90
Early failure rate at 1000h	≤ 5.0 %
Guarantee	3 years

Specification

Energylabel notice	current label, with EPREL registration
Energylabel (G -> A)	E

RL-T8 18 865/G13 EM



Specification

Diameter	26,7 mm
Tube diameter	26 mm
Length max.	603 mm
Length	600 mm
Burning position	any
Mercury content	0.0 mg
Shatterproof	Nie
Photobiological safety according to EN 62471	RG0
Lamp shape	Tube, double-ended
Base	G13
Colour	White

Notes on Operation

Degree of protection (IP)	IP20
Burning position	any
Mode of operation	CCG, 230V
suitable for tandem circuit	Tak
Ambient temperatures	-20 +45 °C
Tc Temperature max.	65 °C
Tc max. with CCG or 230V AC	65 °C
max. temperature at Tc -point for nominal life with CCG or 230V AC	60 °C

Information especially for EPREL

Energylabel notice	current label, with EPREL registration	
Lighting technology	LED	
Mains/Non mains connectable	MLS	
Directional or non-directional light	NDLS	
Color tunable light source	Nie	
Type of color temperature	SINGLE_VALUE	
Color stability MacAdams EPREL	6	
Displacement factor EPREL	0.90	
Life factor EPREL	0.90	
Lumen maintenance EPREL	0.70	
Flicker	1.0	
Stroboscopic effect	0.4	
EPREL ID number	541560	

RL-T8 18 865/G13 EM



Miscellaneous

Similar products


43920127, 43719721, 43719791, 43719849

Notes

T8 LED tube for exchange with FL, daylight, glass bulb, non-dim, base G13. Suitable for serial connection. Please, note installation instructions!

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).




Spectrum


As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.

White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin. Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



LED-Retrofit-Tube-Lampen für Leuchtstofflampen 6500K



Special features









General notes

Please note the installation instructions when replacing fluorescent lamps with LED tubes. Some LED lamp types are only suitable for 1: 1 replacement at the reespective burning position: with CCG by using the enclosed starter, with ECG with compatible control gear. Others can be operated directly on 230V (conversion of the luminaire), others again can 'do' CCG as well as 230V or all 3 variations. Neo tubes need an external LED driver (replacement of the control gear). LED Neo tubes are dimmable, all other LED tubes are not dimmable.

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

RL-T8 18 865/G13 EM



Subject to change without notice. Errors and omissions excepted.

Safety instructions

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.