


Product Datasheet Date: 03.12.2025













2700K





1

,8

200

15 000h

### **General Data**

Article No.	43819833
Kod	RL-PIN20 827/C/G4
Product EAN	4008597198335
Box quantitiy (pcs.)	20
EAN Box	4008597498336
Gross weight of box in kg	0.196
Length of box in m	0.15
Width of box in m	0.122
Height of box in m	0.077
Product weight	3 g
Product status	PhaseOut

## **Electric Parameters**

Wattage	1.8 W	
Nominal power	1.8 W	
Weighted energy consumption in 1000 hours	2 kWh	
Lamp power	1.8 W	
Power factor	> 0.5	



## **Electric Parameters**

Nominal voltage	11.5-12 V
Voltage type	AC
Nominal current	230 mA
Nominal current (mA)	230 mA
Inrush current	17,7 A
max. no. of lamps at 10A automatic fuse	33
max. no. of lamps at 16A automatic fuse	42
dimmable	Nie

## **Light Application Parameters**

Luminous flux	200 lm
Rated lamp luminous flux	200 lm
Luminous flux	200 lm
Beam angle	320 °
Efficacy	111 lm/W
Total mains efficacy	103 lm/W
Light colour	warmwhite
Color temperature	2700 K
Color coordinate X	0.458
Color coordinate Y	0.410
Color rendering index	≥ 80
Color rendering index nominal	80
Color Stability	≤ 6 sdcm

## **Service Life**

Average life	15000 h
Mean service life	15000 h
No. switching cycles	[100000]
Lamp survival factor at 6000h	≥ 0.90
Early failure rate at 1000h	≤ 5.0 %
Guarantee	4 years

## **Specification**

Energylabel notice	current label, with EPREL registration
Energylabel (G -> A)	F
Diameter	13 mm



#### **Specification**

Length	36 mm
Length	36 mm
Burning position	any
Mercury content	0.0 mg
Photobiological safety according to EN 62471	RG1
Lamp shape	Capsule
Base	G4
Colour	White

#### **Notes on Operation**

Degree of protection (IP)	IP20
Burning position	any
Mode of operation	LV transformer
Ambient temperatures	-20 +40 °C

#### Information especially for EPREL

Energylabel notice	current label, with EPREL registration	
Lighting technology	LED	
Color tunable light source	Nie	
Color stability MacAdams EPREL	6	
Life factor EPREL	0.90	
Lumen maintenance EPREL	0.70	
Flicker	1.0	
Stroboscopic effect	0.4	
EPREL ID number	730346	

#### **Miscellaneous**

Similar products	43819832	

#### **Notes**

LED PIN, LED lamp for exchange with pin-base halogen lamps, base G4. LED light does not contain UV or IR radiation.

 $\label{eq:please} \textit{Please, refer to} \ \underline{\textit{www.radium.de/recycling}} \ \textit{for notes on disposal of burned-out lamps as well as lamp breakage}.$ 

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

### Base

G4

IEC/EN 60061-1



sheet 7004-72-3




#### Spectrum


As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.

The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.

White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin. Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



LED-Retrofit-Lamps 2700K



daylight(D 65)

#### Special features







#### General notes

For LED replacement of halogen and incandescent lamps, we recommend direct replacement (1: 1) at the respective burning position. For new systems, the number of lamps in the circuit operated at control gear such as transformers or dimmers can be obtained from corresponding compatibility lists (if available). If there is no specification for the type of device or lamp required, for safety reasons, the replacement power shall be assumed as taht of the original halogen type (eg "RL-MR16 35" -> 35W, independent of the real power consumption).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

#### Safety instructions

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.