LED HPM-Retrofit RL-HRL250 840/C/E40 EM



Product Datasheet Date: 03.12.2025













80

4000K

50 000h

General Data

Article No.	43920522
Kod	RL-HRL250 840/C/E40 EM
Product EAN	4008597205224
Box quantitiy (pcs.)	6
EAN Box	4008597405228
Gross weight of box in kg	5.49
Length of box in m	0.507
Width of box in m	0.356
Height of box in m	0.345
Product weight	560 g
Product status	Aktywne

Electric Parameters

Wattage	80.0 W
Nominal power	80.0 W
Weighted energy consumption in 1000 hours	80 kWh
Lamp power	80.0 W
Nominal voltage	220-240 V

LED HPM-Retrofit

RL-HRL250 840/C/E40 EM



Electric Parameters

Voltage type	AC
Nominal current	345 mA
Nominal current (mA)	345 mA
Inrush current	39 A
max. no. of lamps at 10A automatic fuse	15
max. no. of lamps at 16A automatic fuse	19

Light Application Parameters

Luminous flux	15000 lm
Rated luminous flux according to IEC 62612	15000 lm
Luminous flux	15000 lm
Beam angle	330 °
Efficacy	188 lm/W
Total mains efficacy	188 lm/W
Color temperature	4000 K
Color coordinate X	0.382
Color coordinate Y	0.380
Color rendering index	≥ 80
Color Stability	≤ 6 sdcm

Service Life

Average life	50000 h
Mean service life	50000 h
Min. number of switching cycles	20000
Guarantee	5 years

Specification

Energylabel (G -> A)	В
Diameter	120 mm
Length	288 mm
Length	288 mm
Burning position	any
Material	Glass
Photobiological safety according to EN 62471	RG0
Lamp shape	Other
Base	E40

LED HPM-Retrofit

RL-HRL250 840/C/E40 EM



Specification

	NATI 11
Colour	White

Notes on Operation

Degree of protection (IP)	IP20
Burning position	any
Mode of operation	CCG, 230V
Ambient temperatures	-20 +45 °C

Information especially for EPREL

Lighting technology	LED	
Mains/Non mains connectable	MLS	
Directional or non-directional light	NDLS	
Color tunable light source	Nie	
Type of color temperature	SINGLE_VALUE	
Color stability MacAdams EPREL	6	
Displacement factor EPREL	0,9	
Life factor EPREL	0.9	
Lumen maintenance EPREL	0.93	
Flicker	1.0	·
Stroboscopic effect	0.4	
EPREL ID number	2222273	·

Notes

LEDretrofit f. mercury vapor lamps, non-dim. Operate with contr. gear (1:1 replacemt) or without (230V). Use: outdoor, hall lighting (luminaire w. IP)

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value. The optinal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Base



E40 IEC/EN 60061-1 sheet 7004-24-6

Spectrum

As daylight is a mixture of direct sunlight and light from the sky, the spectral distribution changes all the time due to the time of the day and the weather. The standard illuminant D65 corresponds to daylight with colour temperature of about 6500K.


The colour of coloured LEDs depends on the chemical elements within the light generating chip. The coloured light is generated directly and does not need filtering.

White LEDs are either RGB (red + green + blue chip in one LED = light colour white) or blue LED-chips with yellow/orange phosphor in the resin.


LED HPM-Retrofit RL-HRL250 840/C/E40 EM



Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm)per 10nm.



LED retrofit lamps 4000K



daylight(D 65)

Special features





General notes

When replacing mercury vapor lamps HRL with LED lamps, we recommend replacement at the respective light point with operation at mains voltage directly (disconnect ballast, for lamps with article no. 426...), newer generations may also be replaced 1:1 (ballast remains in luminaire, lamps with article no. 43...) An ambient temperature of the lamp of 60 ° C inside the luminaire must not be exceeded. Outdoor use is permitted (IP65).

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

Safety instructions

To ensure full light efficiency and product life, the permissible temperature ranges must be observed and dry environment ensured. When operated with existing control gear, their compatibility with the lamp must be checked.

All technical data without guarantee.