



## General Data

Article No.	OTNA5123
Kod	DRIVER 75W/24V IP20
Product EAN	4003556015500
Box quantity (pcs.)	50
EAN Box	4003556415508
Gross weight of box in kg	11.26
Length of box in m	0.37
Width of box in m	0.245
Height of box in m	0.2
Product weight	184 g
Product status	<span style="color: green;">●</span> Aktywne

## Electric Parameters

Output power	0-75.0 W
Power factor	0.95
Input voltage AC (range)	198-264 V
Input voltage DC (range)	176-280 V
Output voltage	24 V

## Electric Parameters

Surge voltage resistance (L - N)	1 kV
Number of Channels	1
Standby consumption	0.5 W
Inrush current	44 A
Period of inrush current	192 $\mu$ s
Input current max.	0.49 A
Output current	3130 mA
Mains frequency	0 / 50 / 60 Hz
Suitable for DC-voltage (primary side)	Tak
Content of harmonics (THD)	10 %
max. no. of lamps at 10A-B10 automatic fuse	9
max. no. of lamps at 16A-B16 automatic fuse	15
dimnable	Nie
Dimming with push-button	Nie

## Service Life

Service life	50000 h
Tc Temperature max.	90 °C
Lifetime @Tc low	90000 h
Guarantee	5 years

## Specification

Mean efficiency	88 %
Length	168 mm
Height max.	30 mm
Width	38 mm
Model	Static
Material	PC

## Notes on Operation

Degree of protection (IP)	IP20
Protection class	II
Type of connection	spring clamp
Range of storage temperature	-20 ... +60 °C
Ambient temperatures	-20....+45 °C
Tc Temperature max.	90 °C

## Notes on Operation

---

max. relative air humidity	90 %
----------------------------	------

---

## Information especially for EPREL

---

Standby consumption	0.5 W
---------------------	-------

---

## Miscellaneous

---

Similar products	OTNA3103, OTNA3104, OTNA5124
------------------	------------------------------

---

## Notes

Compact constant voltage LED driver for modules up to 75W, IP20, protection class II, easy to install, DC-compatible.

Please, refer to [www.radium.de/recycling](http://www.radium.de/recycling) for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

### Special features



### General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

® = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.