



LED T5 Neo®, G5



Article number	Name			d mm	l mm		
43720825	RL-T5 14/24 NEO 830/G5 DC	5.7 - 10,0	960 - 1620	17	549	●	D
43720826	RL-T5 14/24 NEO 840/G5 DC	5.7 - 10,0	1060 - 1800	17	549	○	C
43720827	RL-T5 14/24 NEO 865/G5 DC	5.7 - 10,0	1060 - 1800	17	549	●	C
43720828	RL-T5 21/39 NEO 830/G5 DC	10.1 - 17.9	1670 - 2840	17	849	●	D
43720829	RL-T5 21/39 NEO 840/G5 DC	10.1 - 17.9	1850 - 3150	17	849	○	C
43720830	RL-T5 21/39 NEO 865/G5 DC	10.1 - 17.9	1850 - 3150	17	849	●	C
43720831	RL-T5 28/54 NEO 830/G5 DC	13.8 - 24.5	2350 - 4000	17	1149	●	D
43720832	RL-T5 28/54 NEO 840/G5 DC	13.8 - 24.5	2600 - 4400	17	1149	○	C
43720833	RL-T5 28/54 NEO 865/G5 DC	13.8 - 24.5	2600 - 4400	17	1149	●	C
43720834	RL-T5 35/49 NEO 830/G5 DC	13.2 - 23.4	2270 - 3870	17	1449	●	D
43720835	RL-T5 35/49 NEO 840/G5 DC	13.2 - 23.4	2520 - 4300	17	1449	○	C
43720836	RL-T5 35/49 NEO 865/G5 DC	13.2 - 23.4	2520 - 4300	17	1449	●	C
43720837	RL-T5 49/80 NEO 830/G5 DC	19.2 - 33.9	3320 - 5600	17	1449	●	D
43720838	RL-T5 49/80 NEO 840/G5 DC	19.2 - 33.9	3680 - 6200	17	1449	○	C
43720839	RL-T5 49/80 NEO 865/G5 DC	19.2 - 33.9	3680 - 6200	17	1449	●	C



Driver for LED T5 Neo®



Article number	Name			l mm	b mm	h mm
DALI						
1 OTDA4030	DRIVER DC DALI 15W/100-350mA IP20	14,7	16 - 24	100 - 350	195	30
1 OTDA4439	DRIVER DC DALI 37W/200-350mA IP20	37,0	54 - 240	200 - 350	195	30
1 OTDA4441	DRIVER DC DALI 75W/200-350mA IP20	75,0	54 - 240	200 - 350	245	30
ON/OFF						
2 OTNA4435	DRIVER DC 20W/200-350mA IP20	20,0	25 - 57	200 - 350	156	30
2 OTNA4436	DRIVER DC 40W/200-350mA IP20	40,0	58 - 114	200 - 350	195	30
2 OTNA4437	DRIVER DC 60W/200-350mA IP20	60,0	115 - 172	200 - 350	195	30
2 OTNA4438	DRIVER DC 80W/200-350mA IP20	80,0	170 - 230	200 - 350	195	30

Further important data on the products can be found at www.radium.de/en.

Note: Log in to get full access to our product data.

If you have any questions, please contact us at www.radium.de/en/contact-us.

www.radium.de



Radium
Die Lichtmarke



Product news.

November 2025.



LED T8 Neo®, G13



Article number	Name			d mm	l mm		
43719848	RL-T8 18 NEO 840/G13 DC	3.8 - 11,0	716 - 1875	28.5	600	○	C
43719849	RL-T8 18 NEO 865/G13 DC	3.8 - 11,0	690 - 1800	28.5	600	●	D
43719850	RL-T8 36 NEO 840/G13 DC	9.8 - 20.2	1772 - 3418	28.5	1200	○	C
43719851	RL-T8 36 NEO 865/G13 DC	9.8 - 20.2	1744 - 3368	28.5	1200	●	C
43719852	RL-T8 58 NEO 840/G13 DC	20.0 - 30.8	3550 - 5180	28.5	1500	○	C
43719853	RL-T8 58 NEO 865/G13 DC	20.0 - 30.8	3390 - 4925	28.5	1500	●	D



Driver for LED T8 Neo®



Article number	Name				l mm	b mm	h mm
DALI							
1 OTDA4030	DRIVER DC DALI 15W/100-350mA IP20	14.7	16 - 24	100 - 350	195	30	20
1 OTDA4031	DRIVER DC DALI 30W/550-750mA IP20	31.5	54 - 240	200 - 350	285	30	21
1 OTDA4032	DRIVER DC DALI 60W/1100-1500mA IP20	63.0	54 - 240	200 - 350	245	30	21
ON/OFF							
2 OTNA4435	DRIVER DC 20W/200-350mA IP20	14.7	25 - 57	200 - 350	156	30	21
2 OTNA4436	DRIVER DC 40W/200-350mA IP20	29.4	58 - 114	200 - 350	195	30	21
2 OTNA4437	DRIVER DC 60W/200-350mA IP20	50.4	115 - 172	200 - 350	245	30	21

Further important data on the products can be found at www.radium.de/en.

Note: Log in to get full access to our product data.

If you have any questions, please contact us at www.radium.de/en/contact-us.

www.radium.de